

# The New York City Council

## Legislation Details (With Text)

File #: Int 0273-2010 Version: A Name: Lighting of temporary walkways, foot bridges and

sidewalk sheds at construction sites.

Type: Introduction Status: Enacted

In control: Committee on Housing and Buildings

On agenda: 6/9/2010

**Title:** A Local Law to amend the administrative code of the city of New York, in relation to lighting of

temporary walkways, foot bridges and sidewalk sheds at construction sites.

Sponsors: Stephen T. Levin, Charles Barron, Julissa Ferreras-Copeland, Lewis A. Fidler, Vincent J. Gentile, Sara

M. Gonzalez, Letitia James, Brad S. Lander, Michael C. Nelson, Annabel Palma, Domenic M. Recchia, Jr., James G. Van Bramer, Jumaane D. Williams, Margaret S. Chin, Mark S. Weprin, James F. Gennaro, Robert Jackson, Daniel R. Garodnick, Melissa Mark-Viverito, Elizabeth S. Crowley, G.

Oliver Koppell, Diana Reyna, Ydanis A. Rodriguez, Deborah L. Rose

Indexes:

Attachments: 1. Int. No. 273 - 6/9/10, 2. Committee Report 6/22/10, 3. Hearing Testimony 6/22/10 - Bomee Jung, 4.

Hearing Testimony 6/22/10, 5. Hearing Transcript 6/22/10, 6. Committee Report 9/28/10, 7. Committee Report - Stated Meeting, 8. Fiscal Impact Statement, 9. Mayor's Letter, 10. Hearing

Transcript - Stated Meeting 9-29-10, 11. Local Law 51

Date	Ver.	Action By	Action	Result
6/9/2010	*	City Council	Introduced by Council	
6/9/2010	*	City Council	Referred to Comm by Council	
6/22/2010	*	Committee on Housing and Buildings	Hearing Held by Committee	
6/22/2010	*	Committee on Housing and Buildings	Laid Over by Committee	
9/28/2010	*	Committee on Housing and Buildings	Hearing Held by Committee	
9/28/2010	*	Committee on Housing and Buildings	Amendment Proposed by Comm	
9/28/2010	*	Committee on Housing and Buildings	Amended by Committee	
9/28/2010	Α	Committee on Housing and Buildings	Approved by Committee	Pass
9/29/2010	Α	City Council	Approved by Council	Pass
9/29/2010	Α	City Council	Sent to Mayor by Council	
10/6/2010	Α	Mayor	Hearing Held by Mayor	
10/6/2010	Α	Mayor	Signed Into Law by Mayor	
10/6/2010	Α	City Council	Recved from Mayor by Council	

Int. No. 273-A

By Council Members Levin, Barron, Ferreras, Fidler, Gentile, Gonzalez, James, Lander, Nelson, Palma, Recchia, Van Bramer, Williams, Chin, Weprin, Gennaro, Jackson, Garodnick, Mark-Viverito, Crowley, Koppell, Reyna, Rodriguez and Rose

A Local Law to amend the administrative code of the city of New York, in relation to lighting of temporary walkways, foot bridges and sidewalk sheds at construction sites.

#### Be it enacted by the Council as follows:

Section 1. Section BC 3307.2.1 of the New York city building code, as added by local law number 33 for the year 2007, is amended to read as follows:

#### **3307.2.1 Temporary walkways.** Temporary walkways shall comply with the following:

- 1. Temporary walkways shall be of sufficient width to accommodate the pedestrian traffic, but in no case shall it be less than 5 feet (1524 mm) in width, and shall be provided with a durable walking surface.
- 2. All temporary walkways shall be illuminated at all times either by [natural] daylight or [artificial] electric light. The level of illumination shall be [the equivalent of that produced by 200 watt, 3400 lumen minimum, standard incandescent lamps enclosed in vandal-proof fixtures and spaced 15 feet (4572 mm) apart and 8 feet (2438 mm) above the floor level] a minimum of 1 foot-candle (11 lux) measured at the level of the walking surface. All lamps shall be enclosed in vandal-proof fixtures, have a minimum luminous efficacy of 45 lumens per watt or greater and be rated to operate at temperatures of 5 degrees Fahrenheit and higher. [Artificial] Electric lighting units shall be inspected [nightly] daily; and burned out or inoperative units shall be replaced or repaired immediately. Photosensors may be used to control electric lighting according to the amount of daylight available. All photosensors shall be equipped for fail-safe operation ensuring that if the sensor or control fails, the lamps will provide the lighting levels required by this section.
- 3. Temporary walkways shall be provided with adequate slopes so that they are accessible and shall be designed to support all imposed loads, and in no case shall the design live load be less than 150 pounds per square foot (732.3 kg/m²).
- 4. Where permission has been granted by the Department of Transportation to locate a temporary

walkway beyond the curb line, such temporary walkway shall be provided with a guardrail in accordance with the Department of Transportation's requirements.

§2. Section BC 3307.2.2 of the New York city building code, as added by local law number 33 for the year 2007, is amended to read as follows:

### **3307.2.2 Foot bridges.** Foot bridges shall comply with the following:

- 1. Foot bridges shall be of sufficient width to accommodate the pedestrian traffic, but in no case shall it be less than 5 feet (1524 mm) in width, and shall be provided with a durable walking surface.
- 2. All foot bridges shall be illuminated at all times either by [natural] daylight or [artificial] electric light. The level of illumination shall be [the equivalent of that produced by 200 watt, 3400 lumen minimum, standard incandescent lamps enclosed in vandal-proof fixtures and spaced 15 feet (4572 mm) apart and 8 feet (2438 mm) above the floor level] a minimum of 1 foot-candle (11 lux) measured at the level of the sidewalk walking surface. All lamps shall be enclosed in vandal-proof fixtures, shall have a minimum luminous efficacy of 45 lumens per watt or greater, and be rated to operate at temperatures of 5 degrees Fahrenheit and higher. [Artificial] Electric lighting units shall be inspected [nightly] daily; and burned out or inoperative units shall be replaced or repaired immediately. Photosensors may be used to control electric lighting according to the amount of daylight available. All photosensors shall be equipped for fail-safe operation ensuring that if the sensor or control fails, the lamps will provide the lighting levels required by this section.
- 3. Foot bridges shall be provided with adequate slopes so that they are accessible and shall be designed to support all imposed loads and in no case shall the design live load be less than 150 pounds per square foot (732.3 kg/m²). The walkway on such bridge shall be provided with guardrails for its entire length and shall have cleats to prevent slipping. Where planks are used to pave the walkway, they shall be laid close and securely fastened to prevent displacement. Planks shall be of uniform thickness, and all exposed ends on ramps shall be provided with beveled fillers to eliminate tripping

hazards.

- §3. Item 2 of section BC 3307.6.5 of the New York city building code, as added by local law number 33 for the year 2007, is amended to read as follows:
  - 2. The underside of sidewalk sheds shall be lighted at all times either by [natural] daylight or [artificial] electric light. The level of illumination shall be [the equivalent of that produced by 200 watt, 3400 lumen minimum, standard incandescent lamps enclosed in vandal-proof fixtures and spaced 15 feet (4572 mm) apart and 8 feet (2438 mm) above the floor level] a minimum of 1 foot-candle (11 lux) measured at the level of the sidewalk walking surface. All lamps shall be enclosed in vandal-proof fixtures, have a minimum luminous efficacy of 45 lumens per watt or greater, and be rated to operate at temperatures of 5 degrees Fahrenheit and higher. [Artificial]Electric lighting units shall be inspected [nightly] daily; and burned out or inoperative units shall be replaced or repaired immediately. Photosensors may be used to control electric lighting according to the amount of daylight available. All photosensors shall be equipped for fail-safe operation ensuring that if the sensor or control fails, the lamps will provide the lighting levels required by this section.
- §4. This local law shall take effect on July 1, 2011, except that the commissioner of buildings shall take such measures as are necessary for its implementation, including the promulgation of rules, prior to such effective date.

9-21-10 5 pm